

REMARKS

Entry of the foregoing Preliminary Amendment prior to examination is respectfully requested. This Preliminary Amendment amends the specification and the abstract to correct grammatical errors.

In view of the foregoing, favorable examination on the merits is respectfully requested. Should the Examiner believe anything further is desirable in order to place the application in even better condition for allowance, the Examiner is invited to contact Applicants' representative at the telephone number listed below.

Please charge any fee deficiency or credit any over payment to Deposit Account No.18-0013.

Date:

January 7, 2003

Respectfully submitted

By:

Ronald P. Kananen

Ronald P. Kananen

Reg. No. 24,104

RADER, FISHMAN & GRAUER PLLC

1233 20th Street, N.W. Suite 501

Washington, D.C. 20036

Tel: (202) 955-3750

Fax: (202) 955-3751

Customer No. 23353

APPENDIX I

ABSTRACT OF THE DISCLOSURE

The present invention relates to a preamplifier for a computer display for transmitting an analog video signal as a result of converting a digital video signal outputted from a computer by a video D/A converter circuit of a digital signal processing IC to a display, wherein ~~an~~ the input characteristic of the preamplifier is current input to match ~~a~~ the characteristic of current output of the video D/A converter circuit.

SON-2186
80001-2186
REDLINE VERSION



PREAMPLIFIER CIRCUIT

RECEIVED

JAN 10 2003

Technology Center 2800

RECEIVED
JAN -8 2003
TECHNOLOGY CENTER 2800

BACKGROUND OF THE INVENTION

The present invention relates to a preamplifier circuit, and particularly to a preamplifier circuit for color display.

Fig. 5 is a block diagram of a common display system for a computer display. In Fig. 5, reference numeral 2 denotes a preamplifier, reference numeral 3 denotes a main amplifier, and reference numeral 4 designates a CRT.

Fig. 6 is a block diagram of a ~~the~~ display system expected hereafter in a ~~the~~ case where a digital input signal is supplied from a computer proper to the display. In Fig. 6, reference numeral 1 denotes a digital signal processing circuit, reference numeral 2 denotes a preamplifier; reference numeral 3 denotes a main amplifier, reference numeral 4 designates a CRT, reference numeral 5 designates a current-voltage converter circuit, and reference numeral 6

SON-2186
80001-2186
REDLINE VERSION

designates a buffer amplifier.

As shown in Fig. 5, a current computer display receives an analog signal from a computer. The preamplifier 2 mixes the analog signal with an OSD (On Screen Display) signal and a blanking signal. After contrast and brightness are adjusted, the main amplifier 3 amplifies the mixed signal to an amplitude of a few tens of V_{pp} , and then sends the signal to the CRT 4.

With the recent spreading use of ~~an~~ the LCD display, there are some cases where a digital signal is transmitted between the computer and the display as it is without being converted into an analog signal, as shown in Fig. 6. By transmitting ~~a~~ the digital signal between the computer and the display, the display can independently perform various image processing, and also image degradation in ~~a~~ the signal transmission path can be prevented. Thus, the use of such transmission of a digital signal is expected to increase in

SON-2186
80001-2186
REDLINE VERSION

the future.

Fig. 7 shows the details of the circuit configuration between the digital signal processing circuit 1 and the preamplifier 2 in the display system for the computer display shown in the block diagram of Fig. 6. In Fig. 7, reference numeral 1 denotes the digital signal processing IC, reference numeral 2 denotes the preamplifier, reference numeral 5 denotes a load resistance as the current-voltage converter circuit, reference numeral 6 is the buffer amplifier, reference numeral 7 is the wiring capacitance of a substrate pattern, reference numeral 11 is a reference current source, reference numeral 12 designates a video DAC (Digital to Analog Converter), reference numeral 13 designates a reference resistance, and reference numeral 14 designates a direct-current power supply. While Fig. 7 shows circuits for only the R signal of the R, G, and B signals, the same circuits are provided for the G signal and the B signal.

SON-2186
80001-2186
REDLINE VERSION

However, output of the current digital signal processing IC is generally produced by the current output type wide-band video DAC 12, as shown in Fig. 7. On the other hand, the preamplifier 2 generally accepts voltage signal input. Thus, the specifications for the input/output of the digital signal processing IC and the preamplifier are different from each other. Therefore, an output signal current of the digital signal processing IC 1 is converted into a voltage by the load resistance 5, and then the voltage is inputted to the preamplifier 2.

In this case, since the current-voltage conversion is performed by the load resistance 5 external to the IC, stray capacitance becomes larger and frequency characteristics tend to be degraded more than when the current-voltage conversion is performed within the IC. Also, wiring resistance and wiring capacitance of a substrate wiring pattern after the voltage conversion degrade the frequency characteristics in a

SON-2186
80001-2186
REDLINE VERSION

transmission system (since a signal is inputted to the preamplifier 2 via the wiring capacitance 7 of the substrate pattern and a clamp capacitor, the preamplifier 2 side appears to have high impedance when viewed from the digital signal processing IC 1). Because of the high signal band, it is necessary to provide the buffer amplifier 6 between the load resistance 5 and the preamplifier 2 in order to control the degradation in frequency characteristics caused by the substrate pattern wiring capacitance.

As described above, the current output of the digital signal processing IC is converted into a voltage signal by using the external load resistance, and then the voltage signal is inputted to the conventional preamplifier for computer display. Thus, there are the problems of susceptibility to stray capacitance and degradation in frequency characteristics. In order to avoid this, it is necessary to provide the buffer amplifier between the load

SON-2186
80001-2186
REDLINE VERSION

resistance and the preamplifier.

SUMMARY OF THE INVENTION

It is an object of the present invention to realize a preamplifier circuit for a computer display that makes it possible to obtain excellent frequency characteristics without adding extra components to the digital signal processing IC and the preamplifier by a relatively simple method of matching specifications for the output of the digital signal processing IC and the signal input of the preamplifier to each other.

In order to achieve the above objective, according to the present invention, there is provided a preamplifier circuit for a computer display for transmitting an analog video signal as a result of converting ~~a~~ the digital video signal outputted from a computer by a D/A converter circuit to a display, wherein ~~an~~ the input characteristic of the preamplifier circuit is current input to match ~~a~~ the characteristic of

SON-2186
80001-2186
REDLINE VERSION

current output of the D/A converter circuit.

Thus, it is possible to realize a preamplifier circuit for a computer display that makes it possible to obtain excellent frequency characteristics with a relatively small number of components and with reduced susceptibility to stray capacitance.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram of a display system for a computer display using a preamplifier circuit according to the present invention;

Fig. 2 is a detailed diagram of a configuration of a preamplifier circuit according to an embodiment of the present invention and a the digital signal processing circuit in the preceding stage;

Fig. 3 is a detailed diagram of a configuration of a preamplifier circuit according to another embodiment of the

SON-2186
80001-2186
REDLINE VERSION

present invention and ~~a~~the digital signal processing circuit
in the preceding stage;

Fig. 4 is a circuit diagram of a current conversion
circuit employing a transconductance amplifier used in a
preamplifier circuit according to the present invention;

Fig. 5 is a block diagram of a conventional common
display system for a computer display;

Fig. 6 is a block diagram of a display system for a
computer display in ~~a~~the case where a digital output signal
is supplied from a computer proper; and

Fig. 7 is a detaileded diagram of a circuit configuration
between ~~a~~the digital signal processing circuit and ~~a~~the
preamplifier in the configuration of Fig. 6.

DETAILED DESCRIPTION OF THE INVENTION

A preamplifier circuit according to the present invention
will hereinafter be described in detail with reference to the

accompanying drawings.

Fig. 1 is a block diagram of a display system for a computer display using the preamplifier circuit according to the present invention. In Fig. 1, reference numeral 1 denotes a digital signal processing circuit, reference numeral 2 denotes a preamplifier, reference numeral 3 denotes a main amplifier, and reference numeral 4 designates a CRT. The display system has a system configuration in which the current-voltage converter circuit and the buffer amplifier in Fig. 6 are removed by matching the signal input/output specifications of the digital signal processing IC 1 and the preamplifier circuit 2 to each other.

Fig. 2 and Fig. 3 show details of the configuration between the digital signal processing circuit 1 and the preamplifier 2 in the display system for the computer display shown in the block diagram of Fig. 1. While Fig. 2 and Fig. 3 show circuits for only the R signal of the R, G, and B signals,

SON-2186
80001-2186
REDLINE VERSION

the same circuits are provided for the G signal and the B signal. In Fig. 2 and Fig. 3, reference numeral 1 denotes the digital signal processing IC, reference numeral 2 denotes the preamplifier, reference numeral 11 denotes a reference current source, reference numeral 12 designates a video DAC, reference numeral 13 designates a reference resistance, reference numeral 14 designates a direct-current power supply, reference numeral 21 denotes a current conversion circuit, reference numeral 22 denotes a reference resistance, and reference numeral 23 denotes a direct-current power supply.

A problem in realizing current input of the preamplifier 2 is to prevent the effects of variations and temperature characteristics of ~~an~~ the internal resistance used to convert ~~a~~ the signal current into a voltage in the preamplifier from being produced on the output signal amplitude.

The present invention solves this problem by supplying a

SON-2186
80001-2186
REDLINE VERSION

reference current (IREF) from the digital signal processing IC 1 to the preamplifier 2, as shown in Fig. 2, or generating a reference current (IREF) within the preamplifier 2 using the external reference resistance 22 of the preamplifier 2, as shown in Fig. 3, and then providing the current conversion circuit 21 formed by using the reference current (IREF) and the internal resistance within the preamplifier 2.

The conversion circuit 21 can be realized by a transconductance amplifier employing pairs of transistors, as shown in Fig. 4, whose characteristics coincide with each other and using the change in transconductance of the transistors.

In Fig. 4, I_{ref} is a reference current (IREF) that is dependent on external resistance (having variations and temperature characteristics much less significant than those of internal resistance of the IC), whereas I_{in} is a current that is dependent on the internal resistance of the IC. A

SON-2186
80001-2186
REDLINE VERSION

video signal inputted to an IN+/IN- terminal is passed through the transconductance amplifier and then outputted from an OUT terminal. The video signal inputted to the IN+/IN- terminal has been subjected to current-voltage conversion by the internal resistance of the preamplifier IC before inputted to the circuit of Fig. 4 and, thus, has become a voltage signal. However, since the input impedance of the transconductance amplifier is low, the current-voltage conversion is also performed by the low resistance, and current input can be realized by lowering the input resistance of the preamplifier

2.

Letting ΔV_{in} be a ~~the~~ differential voltage of the IN+ and IN- terminals, ΔV be a ~~the~~ differential voltage between bases of a transistor Q5 and a transistor Q6, and ΔV_{out} be a ~~the~~ voltage variation of the OUT terminal in the circuit of Fig. 4,

$$\Delta V = 2r_e \{ \Delta V_{in} / (R_1 + 2r_e) \} \quad (1)$$

SON-2186
80001-2186
REDLINE VERSION

where r_e is the emitter resistance of transistors Q1, Q2, Q3, and Q4, and $r_e = V_t/I_{iref}$ (where V_t is thermal voltage of the transistors).

$$\Delta V_{out} = R_3 \{ \Delta V / (2r_e') \} \quad (2)$$

where r_e' is emitter resistance of the transistors Q5 and Q6, and $r_e' = V_t/I_{in}$.

The equation (1) is substituted into the equation (2).

$$\begin{aligned} \Delta V_{out} &= R_3 [2r_e \{ \Delta V_{in} / (R_1 + 2r_e) \} / (2r_e')] \\ &= (R_3/R_1) (r_e/r_e') \Delta V_{in} \\ &= (R_3/R_1) \{ (V_t/I_{iref}) / (V_t/I_{in}) \} \Delta V_{in} \\ &= (R_3/R_1) (I_{in}/I_{iref}) \Delta V_{in} \end{aligned} \quad (3)$$

where since $R_1 \gg 2r_e$, $R_1 + 2r_e \approx R_1$.

When I_{iref} and I_{in} are generated from a constant voltage V_{ref} by the external resistance R_{out} and the internal resistance R_{in} of the IC, respectively, I_{iref} and I_{in} are expressed by the following equations—:

$$I_{iref} = V_{ref}/R_{out} \quad (4)$$

$$I_{in} = V_{ref}/R_{in} \quad (5)$$

When letting $A \cdot I_{iref}$ be an input signal current from the digital signal processing IC (reference current is generated similarly to I_{iref} of the preamplifier), and performing voltage conversion by the resistance R_{in} within the preamplifier, ΔV_{in} is expressed by the following equation—:

$$\Delta V_{in} = A \cdot I_{iref} \cdot R_{in} \quad (6)$$

From the equations (3) to (6),

$$\begin{aligned} \Delta V_{out} &= (R_3/R_1) \cdot \{(V_{ref}/R_{in}) / (V_{ref}/R_{out})\} \\ &\quad \cdot A \cdot I_{iref} \cdot R_{in} \\ &= (R_3/R_1) \cdot \{(V_{ref}/R_{in}) / (V_{ref}/R_{out})\} \\ &\quad \cdot A \cdot (V_{ref}/R_{out}) \cdot R_{in} \\ &= (R_3/R_1) \cdot A \cdot V_{ref} \end{aligned} \quad (7)$$

The resistance R_1 and the resistance R_3 are the internal resistances of the IC—; and, it can be considered from the equation (7) that although the resistance R_1 and the resistance R_3 have temperature characteristics and variations,

the temperature characteristics and the variations of the resistance R1 and the resistance R3 cancel each other out. Therefore, it is understood that the effects of the temperature characteristics and the variations are not produced on output amplitude.

Thus, the present invention has the following effects.—:___

1) By unifying the specifications for the signal output of the digital signal processing IC and the signal input of the preamplifier, the output of the digital signal processing IC can be connected as it is to the preamplifier input. Therefore, an intermediate circuit is not required, whereby the number of parts can be reduced.—;___

2) By making signal transmission between the digital signal processing IC and the preamplifier by current rather than voltage, degradation in the frequency characteristics caused by stray capacitance, substrate pattern wiring capacitance and the like can be controlled. Therefore, it is

SON-2186
80001-2186
REDLINE VERSION

possible to increase the degree of freedom of parts arrangement, wire routing and the like in substrate design.—; and

3) By providing the current conversion circuit using the transconductance amplifier having a low input impedance in the preamplifier, it is possible to prevent the effects of temperature characteristics and variations of the internal resistance of the IC from being produced on the output signal amplitude of the preamplifier. Thus, a circuit configuration suitable for higher IC integration can be provided.

While preferred embodiments of the present invention have been described using specific terms, such description is for illustrative purposes only, and it is to be understood that changes and variations may be made without departing from the spirit or scope of the following claims.

SON-2186
80001-2186
REDLINE VERSION

ABSTRACT OF THE DISCLOSURE

The present invention relates to a preamplifier for a computer display for transmitting an analog video signal as a result of converting a digital video signal outputted from a computer by a video D/A converter circuit of a digital signal processing IC to a display, wherein ~~an~~ the input characteristic of the preamplifier is current input to match a the characteristic of current output of the video D/A converter circuit.

SON-2186
80001-2186
REDLINE VERSION

Figs. 1, 5, 6

1a: RGB signal input (from computer)

1b: OSD signal/Blanking signal

1: Digital signal processing circuit

5: Current-voltage converter circuit

Figs. 2, 3, 7

2a: Same for Gch and Bch

1: Digital signal processing circuit

7: Substrate pattern wiring capacitance

14, 23: Power supply

21: Current conversion circuit